



[promultis]

outdoortotem2

- Weather-proof IP rated steel enclosure
- Vandal-proof
- High brightness, 2500 nits LED display
- 10 touch, Projective Capacitive
- Range of sizes and styles
- Built-in Air Conditioning
- Large access doors with locks
- Compliance with FCC and CE
- Bespoke enclosures available



**Outdoor Totem 2**

10 Touch	47"	55"
----------	-----	-----

**Outdoor Totem 2 (double sided)**

10 Touch	47"	55"
----------	-----	-----



[promultis] outdoortotem2

For more exciting multitouch products visit  
[www.promultis.info](http://www.promultis.info)  
 or call +44 (0) 239 251 2794

# Outdoor Totem2 Specification

## TOTEM CHASSIS

Waterproof grade	IP65
Installation	Wall mount, hanging and free standing (fixed on ground)
Front tempered and anti-glare glass	6mm AR safety glass
Temperature control system	Intelligent and changes in temperature
Built-in air conditioning	Adapted to -40°C--+60°C environment temperature
Intelligent light system	Auto adjusts brightness according to environment light, saving energy
Audio output	Stereo L/R, 5W*2, 8Ω
Power supply	AC 110V - 240V, 50/60HZ

## TOUCH TECHNOLOGY

Detection method	Projective Capacitive
Touch	10 touch points
Touch sensitive to:	Finger, Opaque object, Stylus
Sunlight Sensitivity	Can be used in direct sunlight
Interpolation	32,768x32,768
Response time	Repeated touch <6ms
Drift	None
Temperature	-20°C~60°C
Accuracy	±2mm
Interface	USB-2
Relative Humidity	10%~90%RH
Supported OS	Windows, MAC, Linux, Android

## PANEL

Diagonal Size	47" & 55"
Glass type	Toughened full transmittivity
Panel resolution	1920 x 1080
Native resolution	1920 x 1080 60Hz
Brightness (nits)	2500 nits
Contrast ratio	1500 to 1
Response time	6ms
Aspect ratio	16x9
Display colours	16.7M
Viewing angle	horizontal / vertical 178° / 178°
Pixel pitch	0.744 (mm)
LCD Illumination	Backlit LED

