



[promultis]

outdoortotem3

High definition picture quality
Intelligent temperature control system
High-fidelity quality sound
Easy 178 degrees viewing angles



- **Cabinet Design:**
Professional, sleek new design while keeping you screen visible.
- **Brightness:**
High brightness panels are available for direct sunlight visibility.
- **Light sensor:**
Auto-adjust brightness control according to the ambient light.
- **Temperature Control:**
Smart temperature technology will insure a constant even temperature inside the unit. Keeping the panel dry, preventing fog and condensation.
- **Weather:**
IP55 and IP65 rated to insure a dust and water free cabinet.
- **Glass:**
6mm secure tempered front glass for best protection with anti-glare option.



[promultis] outdoortotem3

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794

Outdoor Totem3 Specification

Screen	47"	55"	65"
Resolution	1920 x 1080 DPI	1920 x 1080 DPI	1920 x 1080 DPI
Display Area	1039.68(H)x584.82(V) mm	1209.6(H)x680.4(V) mm	1428.48 (H) x 803.52 (V) mm
Dot pitch	0.63mm(H) x 0.63mm(V)	0.63mm(H) x 0.63mm(V)	0.63mm(H) x 0.63mm(V)
Viewing Angle	H178, V178	H178, V178	H178, V178
Brightness	≥1500cd/m2	≥1500cd/m2	≥1500cd/m2
Contrast Ratio	≥4000:1	≥4000:1	≥4000:1
Colors	16.7M	16.7M	16.7M
Response time	≥60000 hours	≥60000 hours	≥60000 hours
Lifetime	5ms	5ms	5ms
Power	AC 100-240V (50/60Hz)	AC 100-240V (50/60Hz)	AC 100-240V (50/60Hz)
Power consumption	<600W	<600W	<600W
Standby power	<3W	<3W	<3W
Working temperature	40°C~55°C	-40°C~55°C	-40°C~55°C
Working humidity	20%~80%	20%~80%	20%~80%
Frame	Unique safe design	Unique safe design	Unique safe design
Glass	6mm anti-vandal tempered glass, avoid scratches	6mm anti-vandal tempered glass, avoid scratches	6mm anti-vandal tempered glass, avoid scratches
Back frame	Black steel plate	Black steel plate	Black steel plate
Product size	2053.2 x 760 x 240(mm)	2100 x 880 x 230(mm)	2280 x 1003.1 x 230(mm)