



[promultis]

Ascentia Outdoor Totem



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794



Promultis Ascentia Outdoor Totems are ideal for:

- Retail environments and shopping malls
- Marketing Suites
- Local Government
- Events and Exhibition Stands
- Transportation Hubs
- Museum & Galleries

Engage, inform and entertain customers with

- Promotions and incentive campaigns
- Current events and local information
- Way-finding and directional signage
- Interactive multimedia
- Demographic Analytics & Feedback



Colourways and applied graphics

We can also apply a custom vinyl wrap to the casing to promote your company branding and promotions with appropriate colourways and graphics.



Integrated webcams and printer

Some of our Outdoor Totems have webcams and printers. Immerse Interactive software can take advantage of a whole host of photo and video features including green screen. The built-in printing facility allows users to get a printout of their composite picture.



Immerse Bespoke Interactive Software from Promultis

Promultis offers a bespoke software creation service where our software development team will create a multitouch interactive experience to run on your touch table. Visit our website at <https://immerse.promultis.info/> for example applications and case studies.

CHASSIS FEATURES	
Panel size	43" TFT-LCD
Display area(mm)/mode	943.2mm(H) x 531.4mm(W) 16:9
Maximum resolution	1920 x 1080
Display color	16.7M
Pixel Pitch(mm)	0.63mm(H) x 0.63mm(V) (mm)
Brightness (nits) options	1500cd/m ² 2500cd/m ² 3500cd/m ²
Contrast	4000:1
Visual angle	178°/178°
Response time	6.5ms
Life(hrs)	>60,000(hrs)
INPUT AND OUTPUT	
VGA	1
HDMI	1
USB2.0	1
Audio(L/R) input	1
Audio(L/R) output	1
Speaker	2×10W (8 ohm)
VIDEO	
Color system	PAL
Remote controller	Yes
POWER	
Power supply	AC100~240V 50 /60 HZ
Maximum power consumption	≤ 3600W
Standby power consumption	<5W


TEMPERATURE	
Working temperature	0°C 50°C
Storage temperature	- 35°C ~ 50°C
Working humidity	85%
Storage humidity	85%
Waterproof grade	Outdoor IP65
Temperature control	Fan cooling as standard or air-conditioning as option
FUNCTIONS	
Video format	MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio format	Wave/MP3/WMA/AAC
Image format	JPEG/BMP/TIFF/PNG/GIF
Image resolution	480P/720P/1080P
Split screen display	0.63mm(H) x 0.63mm(V) (mm)
Running subtitle	editable
APPEARANCE	
Panel	White, black, customised
Material	Metal case SPCC
Installation	flood-standing / wall mounted
SERVICE & WARRANTY	
1 year on-site warranty as standard	
Extended warranties and SLA's available at an additional cost	

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

43" Outdoor Totem



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794

CHASSIS FEATURES	
Panel size	49" TFT-LCD
Display area(mm)/mode	1078.8mm(H) x 609mm(W) 16:9
Maximum resolution	1920 x 1080
Display color	16.7M
Pixel Pitch(mm)	0.63mm(H) x 0.63mm(V) (mm)
Brightness (nits) options	1500cd/m ² 2500cd/m ² 3500cd/m ²
Contrast	4000:1
Visual angle	178°/178°
Response time	6.5ms
Life(hrs)	>60,000(hrs)
INPUT AND OUTPUT	
VGA	1
HDMI	1
USB2.0	1
Audio(L/R) input	1
Audio(L/R) output	1
Speaker	2×10W (8 ohm)
VIDEO	
Color system	PAL
Remote controller	Yes
POWER	
Power supply	AC100~240V 50 /60 HZ
Maximum power consumption	≤ 3600W
Standby power consumption	<5W


TEMPERATURE	
Working temperature	0°C 50°C
Storage temperature	- 35°C ~ 50°C
Working humidity	85%
Storage humidity	85%
Waterproof grade	Outdoor IP65
Temperature control	Fan cooling as standard or air-conditioning as option
FUNCTIONS	
Video format	MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio format	Wave/MP3/WMA/AAC
Image format	JPEG/BMP/TIFF/PNG/GIF
Image resolution	480P/720P/1080P
Split screen display	0.63mm(H) x 0.63mm(V) (mm)
Running subtitle	editable
APPEARANCE	
Panel	White, black, customised
Material	Metal case SPCC
Installation	flood-standing / wall mounted
SERVICE & WARRANTY	
1 year on-site warranty as standard	
Extended warranties and SLA's available at an additional cost	

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

49" Outdoor Totem



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.




[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794



[promultis]

49" Outdoor Totem Double-sided



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794

CHASSIS FEATURES	
Panel size	55" TFT-LCD
Display area(mm)/mode	1209.6mm(H) x 680.4mm(W) 16:9
Maximum resolution	1920 x 1080
Display color	16.7M
Pixel Pitch(mm)	0.63mm(H) x 0.63mm(V) (mm)
Brightness (nits) options	1500cd/m ² 2500cd/m ² 3500cd/m ²
Contrast	4000:1
Visual angle	178°/178°
Response time	6.5ms
Life(hrs)	>60,000(hrs)
INPUT AND OUTPUT	
VGA	1
HDMI	1
USB2.0	1
Audio(L/R) input	1
Audio(L/R) output	1
Speaker	2×10W (8 ohm)
VIDEO	
Color system	PAL
Remote controller	Yes
POWER	
Power supply	AC100~240V 50 /60 HZ
Maximum power consumption	≤ 3600W
Standby power consumption	<5W


TEMPERATURE	
Working temperature	0°C 50°C
Storage temperature	- 35°C ~ 50°C
Working humidity	85%
Storage humidity	85%
Waterproof grade	Outdoor IP65
Temperature control	Fan cooling as standard or air-conditioning as option
FUNCTIONS	
Video format	MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio format	Wave/MP3/WMA/AAC
Image format	JPEG/BMP/TIFF/PNG/GIF
Image resolution	480P/720P/1080P
Split screen display	0.63mm(H) x 0.63mm(V) (mm)
Running subtitle	editable
APPEARANCE	
Panel	White, black, customised
Material	Metal case SPCC
Installation	flood-standing / wall mounted
SERVICE & WARRANTY	
1 year on-site warranty as standard	
Extended warranties and SLA's available at an additional cost	

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

55" Outdoor Totem Single-sided



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.




[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794



[promultis]

55" Outdoor Totem Dual-sided



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]
MULTITOUCH SOLUTIONS


For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794



[promultis]

55" Outdoor Totem

with built-in camera and printer



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794

CHASSIS FEATURES	
Panel size	65" TFT-LCD
Display area(mm)/mode	1428.5mm(H) x 803.5mm(W) 16:9
Maximum resolution	1920 x 1080
Display color	16.7M
Pixel Pitch(mm)	0.63mm(H) x 0.63mm(V) (mm)
Brightness (nits) options	1500cd/m ² as standard and up to 3500cd/m ²
Contrast	3500:1
Visual angle	178°/178°
Response time	5ms
Life(hrs)	>60,000(hrs)
INPUT AND OUTPUT	
VGA	1
HDMI	1
USB2.0	2
Audio(L/R) input	1
Audio(L/R) output	1
Speaker	2×10W (8 ohm)
VIDEO	
Color system	PAL
Remote controller	Yes
POWER	
Power supply	AC100~240V 50 /60 HZ
Maximum power consumption	≤ 360W
Standby power consumption	<5W


TEMPERATURE	
Working temperature	0°C 50°C
Storage temperature	- 35°C ~ 50°C
Working humidity	85%
Storage humidity	85%
Waterproof grade	Outdoor IP65
Temperature control	Fan cooling as standard or air-conditioning as option
FUNCTIONS	
Video format	MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio format	Wave/MP3/WMA/AAC
Image format	JPEG/BMP/TIFF/PNG/GIF
Image resolution	480P/720P/1080P
Split screen display	0.63mm(H) x 0.63mm(V) (mm)
Running subtitle	editable
APPEARANCE	
Panel	White, black, customised
Material	Metal case SPCC
Installation	flood-standing / wall mounted
SERVICE & WARRANTY	
1 year on-site warranty as standard	
Extended warranties and SLA's available at an additional cost	

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

65" Outdoor Totem



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.




[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794



[promultis]

65" Outdoor Totem double-sided



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.




[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794



[promultis]

65" Outdoor Totem with built-in camera and printer



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794

CHASSIS FEATURES	
Panel size	75'' TFT-LCD
Display area(mm)/mode	1428.5mm(H) x 803.5mm(W) 16:9
Maximum resolution	1920 x 1080
Display color	16.7M
Pixel Pitch(mm)	0.63mm(H) x 0.63mm(V) (mm)
Brightness (nits) options	1500cd/m ² as standard and up to 3500cd/m ²
Contrast	3500:1
Visual angle	178°/178°
Response time	5ms
Life(hrs)	>60,000(hrs)
INPUT AND OUTPUT	
VGA	1
HDMI	1
USB2.0	2
Audio(L/R) input	1
Audio(L/R) output	1
Speaker	2×10W (8 ohm)
VIDEO	
Color system	PAL
Remote controller	Yes
POWER	
Power supply	AC100~240V 50 /60 HZ
Maximum power consumption	≤ 360W
Standby power consumption	<5W


TEMPERATURE	
Working temperature	0°C 50°C
Storage temperature	- 35°C ~ 50°C
Working humidity	85%
Storage humidity	85%
Waterproof grade	Outdoor IP65
Temperature control	Fan cooling as standard or air-conditioning as option
FUNCTIONS	
Video format	MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio format	Wave/MP3/WMA/AAC
Image format	JPEG/BMP/TIFF/PNG/GIF
Image resolution	480P/720P/1080P
Split screen display	0.63mm(H) x 0.63mm(V) (mm)
Running subtitle	editable
APPEARANCE	
Panel	White, black, customised
Material	Metal case SPCC
Installation	flood-standing / wall mounted
SERVICE & WARRANTY	
1 year on-site warranty as standard	
Extended warranties and SLA's available at an additional cost	

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

75" Outdoor Totem



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.




[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794



[promultis]

75" Outdoor Totem dual-sided



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794

CHASSIS FEATURES	
Panel size	84'' TFT-LCD
Display area(mm)/mode	1865mm(H) x 1052mm(W) 16:9
Maximum resolution	1920 x 1080
Display color	16.7M
Pixel Pitch(mm)	0.63mm(H) x 0.63mm(V) (mm)
Brightness (nits) options	1500cd/m ² as standard and up to 3500cd/m ²
Contrast	3500:1
Visual angle	178°/178°
Response time	5ms
Life(hrs)	>60,000(hrs)
INPUT AND OUTPUT	
VGA	1
HDMI	1
USB2.0	2
Audio(L/R) input	1
Audio(L/R) output	1
Speaker	2×10W (8 ohm)
VIDEO	
Color system	PAL
Remote controller	Yes
POWER	
Power supply	AC100~240V 50 /60 HZ
Maximum power consumption	≤ 360W
Standby power consumption	<5W


TEMPERATURE	
Working temperature	0°C 50°C
Storage temperature	- 35°C ~ 50°C
Working humidity	85%
Storage humidity	85%
Waterproof grade	Outdoor IP65
Temperature control	Fan cooling as standard or air-conditioning as option
FUNCTIONS	
Video format	MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio format	Wave/MP3/WMA/AAC
Image format	JPEG/BMP/TIFF/PNG/GIF
Image resolution	480P/720P/1080P
Split screen display	0.63mm(H) x 0.63mm(V) (mm)
Running subtitle	editable
APPEARANCE	
Panel	White, black, customised
Material	Metal case SPCC
Installation	flood-standing / wall mounted
SERVICE & WARRANTY	
1 year on-site warranty as standard	
Extended warranties and SLA's available at an additional cost	

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

84" Outdoor Totem



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794