




[promultis]

TAB Box Top Touch Screen

Offering Full HD 1080p or 4k, the picture quality is excellent and the touch response is superb. The screen is perfect for Business, Education and Commercial use.



High Brightness screens available



Wall Bracket Included



Optional OPS PC




Interactive UBoardMate Whiteboard Software



100 Touch Points, 4K UHD



Projected Capacitive Technology



43" | 55" | 65" | 75" | 85" screens



HDMI, VGA, RS232 and USB Connectivity



3 Year On-site Warranty



[promultis]
MULTITOUCH SOLUTIONS

For more exciting multitouch products visit
www.promultis.info
or call +44 (0) 239 251 2794


CHASSIS FEATURES	
Materials	Aluminum
Glass type	Toughened
PANEL	
Interactive area	43" 48" 55" 65" 75" 85"
Panel resolution	4K UHD 3840 x 2160
Native resolution	3840 x 2160 60Hz
Brightness (nits)	450
Contrast ratio	1500 to 1
Response time	6ms
Aspect ratio	16x9
Viewing angle	178° / 178°
Pixel pitch	0.744 (mm)
LCD Illumination	Backlit LED
Speaker	10W x2
ENVIRONMENT	
Operating temperature	50°F to 104°F (10°C to 40°C)
Operating Humidity	10% to 80%, non-condensing
Storage Temperature	-4°F to 113°F (-20°C to 45°C)
Storage Humidity	5% to 95%, non-condensing
SHIPPED WITH	
Cables	Power USB HDMI
Remote control	Included
User manual	Included
WARRANTY	
3 year on-site warranty as standard	
Extended warranties and SLA's available at an additional cost	

PROJECTED CAPACITIVE	
Detection method	Projected Capacitive
Input method	Finger and gloved finger
Number of simultaneous touches	10 or 100 touch points
Noise Shielding	DISPLAX XTR-Shield™ Plus, a proprietary noise filtering technology
Aspect ratio	16:9
Controller	Printed circuit board with mini USB connector
Adhesive	Permanent
Interface	HID
OS with multitouch	Windows 8.1, 8, 7, 10; Ubuntu 12.04; Android; Chrome OS
OS with single touch	Mac OS X Yosemite
OS with mouse emulation	Spinetix Media Player HMP 200
Data connectivity	USB 2.0
Touch accuracy	1mm absolute
PERFORMANCE	
Substrate thickness	Up to 6mm
Touch response	5 milliseconds
Calibration	Available using control panel: no drift
POWER CONSUMPTION	
Average power consumption (P)	USB powered @ 5V
	Peak consumption: 410 mA
	Operation consumption: 370mA
RELIABILITY	
Operating temperature range	-20°C to 70°C
Operating humidity range	0% to 96%
Life time expectancy	Unlimited
Controller life time expectancy	1 million hours

TAB Screen Mounting Bracket

Supplied Mounting Bracket


Width	Height	Depth	Weight
960 mm	240 mm	29.4 mm	8kg





[promultis]


55" TAB Box Top Projected Capacitive Touch Screen





[promultis]


65" TAB Box Top Projected Capacitive Touch Screen





[promultis]

75" TAB Box Top Projected Capacitive Touch Screen





[promultis]

85" TAB Box Top Projected Capacitive Touch Screen

