Promultis Varitilt Elite

The Promultis Varitilt Pro is an Electric Height & Tilt Adjustable, Mobile Interactive Table. Screen Sizes of 65"/75"/85", 40 or 100 Touch Points, and Object Recognition Ready Options









CHASSIS FEATURES		
Materials	Aluminium	
Glass Type	Toughened	
Tray	Cable Management & PC Shelf	
Mobility	4 Professional Floor Levelling Castors	
PANEL		
Interactive Area	65" 75" 85"	
Panel Resolution	4K UHD	
Native Resolution	3840 x 2160 60Hz	
Brightness (Nits)	450	
Contrast Ratio	1500:1	
Response Time	6ms	
Aspect Ratio	16 x 9	
Viewing Angle	178 °/178 °	
Pixel Pitch	0.744 (mm)	
LCD Illumination	Backlit LED	
Speaker	10W x2	
ENVIRONMENT		
Operating Temperature	50°F to 104°F (10°C to 40°C)	
Operating Humidity	10% to 80%, non-condensing	
Storage Temperature	-4°F to 113°F (-20°C to 45°C)	
Storage Humidity	5% to 95%, non-condensing	







PROJECTED CAPACITIVE		
Detection Method	Projected Capacitive	
Input Method	Finger / Gloved Finger	
Number of Simultaneous Touches	40 or 100 Touches	
Noise Shielding	DISPLAX XTR-Shield Plus, a proprietary noise filtering technology	
Aspect Ratio	16:9	
Controller	Printed Circuit Board with Mini USB Connector	
Adhesive	Permanent	
Interface	HID	
OS with Multitouch	Windows 8.1, 8, 7, 10; Ubuntu 12.04; Android; Chrome OS	
OS with Single Touch	Mac OS X Yosemite	
OS with Mouse Emulation	Spinetix Media Player HMP 200	
Data Connectivity	USB2.0	
Touch Accuracy	1mm Absolute	
PERFORMANCE		
Substrate Thickness	Up to 6mm	
Touch Response	5 milliseconds	
Calibration	Available Using Control Panel: No Drift	
POWER CONSUMPTION		
Average Power Consumption	USB Powered @ 5V	
	Peak Consumption: 410mA	
	Operation Consumption: 370mA	







RELIABILITY		
Operating Temperature Range	-20°C to 70°C	
Operating Humidity Range	0% to 96%	
Life Time Expectancy	Unlimited	
Controller Life Time Expectancy	1 million hours	
SHIPPED WITH		
Cables	Power / HDMI / USB	
Remote Control	Included	
WARRANTY		
3 Year Warranty		





























